

Technical data

	Certified values fireplace insert	Measured values for accumulation operation	Measured values for convection operation
Energy label of the fireplace insert	A+ UKA 35/60/35/50		
Operating data			
Nominal heat power	7 kW	----	8 kW
Efficiency	> 80 %	> 80 %	> 80 %
Consumption of wood	2,2 kg/h	7 kg (3,5 + 3,5 kg)	2,5 kg/h
Total heat output of the burning chamber ¹	----	28 kW	----
Average heat output ²	----	5,6 kW	----
Heat radiation period ³	----	5 hours	----
Mass flow of flue gas	7 g/s	12 g/s	8 g/s
Required chimney pressure	12 Pa	12 Pa	12 Pa
Required amount of combustion air	20 m ³ /h	30 m ³ /h	25 m ³ /h
Average flue gas temperature on the output	270 °C	219 °C	253 °C
Heat distribution			
Surroundings and convection	56 %	56 %	56 %
door glass (single, double)	44 / - %	44 / - %	44 / - %
General technical information			
Tested according to	EN 13229	----	----
Meets values	1. BImSchV (Stufe2), 15a BVG	----	----
Total weight	----	538 kg	508 kg
Overall dimensions (width x depth x height)	----	771 x 612 x 1872 mm	
Burning chamber dimensions (width x depth)	----	390 x 205 mm	
Combustion air connection	----	from the back / bottom Ø 125 mm	
Flue connection diameter	----	from the back / top Ø 180 mm	
Minimal distances			
from walls made of non-combustible materials			
rear	----	20 mm	
rear with outer thermal shielding	----	0 mm	
to the ceiling	----	400 mm	
to the floor	----	0 mm	
from walls made of combustible materials			
rear	----	50 mm	
rear with outer thermal shielding	----	10 mm	
to the ceiling	----	600 mm	
to the floor	----	0 mm	
Technical data of the surroundings material			
Thermal resistance	----	up to 150 °C	
Thermal conductivity (100 °C)	----	1,374 W/mK	
Specific heat (100 °C)	----	0,247 Cal/g°C	
Volume heat capacity	----	1486 kJ/m ³ K	
Density	----	1490 - 1610 g/dm ³	
Bending strength	----	3,5 - 4,2 MPa	
Compression strength	----	11,0 - 14,0 MPa	
Shrinkage	----	0,088 %	

- 1 With maximum amount of wood of 4 kWh/kg, without taking efficiency losses into account.
- 2 Accumulation operation, specified fuel dose for accumulation period with system efficiency > 80 %.
- 3 The time from ignition to reaching 25% of the maximum average surface temperature compared to room temperature.

BLOX U77

